APBA Vintage and Historic Division Outboard Safety Inspection Checklist

		P	loat No	mber	Roat Name	
		C	owner:			APBA Number:
	Ρ	F	N/A	Note	Helmet	Applicable Snell, Condition, Proper color, No camera
	Ρ	F	N/A	Note	Eye Protection	Full face shield or OSHA Approved eyewear
5	Ρ	F	N/A	Note	Life Jackets	Proper type for boat, Color, Certification tag, Good condition
sarety	Ρ	F	N/A	Note	Drivers Suit	Long Sleeved with closed cuffs, Long Pants with closed cuffs
n	Ρ	F	N/A	Note	Drivers Suit	No flammable synthetic materials
	Ρ	F	N/A	Note	Drivers Suit	Closed toed shoes
	Ρ	F	N/A	Note	Fire Extinguisher	5 Lb. at trailer, Readily available
	Р	F	N/A	Note	Throttle	Return spring on both ends
	Р	F	N/A	Note	Throttle	Proper operation, No locking mechanism
	Р	F	N/A	Note	Engine Mounts	Properly bolted or clamped, Secure
Ð	Р	F	N/A	Note	Tie Downs	Present and secure to prevent kick up (non-hydraulic)
Engine	Р	F	N/A	Note	Swivel Pin	Check for free play and overall tightness of assembly
Ч	Р	F	N/A	Note	Trim Ram	(Hydraulic) Check for free play
	Р	F	N/A	Note	Power Trim	Check for proper function
	Р	F	N/A	Note	Jack Plate	Check for proper function
	Р	F	N/A	Note	Engine	Size and power appropriate to class
	Р	F	N/A	Note	Cockpit	Properly sized for exit or removeable and securely mounted
bit	Ρ	F	N/A	Note	Cables, Pulleys, Chains	Acceptable condition and routing
Cockpit	Ρ	F	N/A	Note	Turnbuckles	Safety wired
ວິ	Ρ	F	N/A	Note	Kill Switch	Properly wired to halt engine and fuel pump
	Ρ	F	N/A	Note	General	Free of sharp objects and padded where needed
	Р	F	N/A	Note	Turn Fins	Acceptable condition with solid, structural mounting
	P	F	N/A	Note	Battery	Properly secured, Acceptable cable routing
	P	F	N/A	Note	Ballast	Properly secured
T	P	F	N/A	Note	Lifting Points	Acceptable condition, full ring, and securely mounted
	P	F	N/A	Note	General	Acceptable condition
	-					
_	Р	F	N/A	Note	Steering Wheel	Secure - installs and removes properly
Cell	Ρ	F	N/A	Note	Seat Belts	Minimum 5 point harness, properly installed, release verified
Ę	Ρ	F	N/A	Note	Cockpit	No protruding sharp edges around driver or entrance
Reinforced Safety	Ρ	F	N/A	Note	Cockpit	Padding around driver - side, back, legs, behind head
σ	Ρ	F	N/A	Note	Seat	Seating position correct, provides lower back support
e S	Ρ	F	N/A	Note	Switches	Engine & fuel kill switches operable from outside, properly labelled
uto	Р	F	N/A	Note	Head Clearance	2" minimum to hard surface
le l	Р	F	N/A	Note	Radio	In place, operates properly
-	Ρ	F	N/A	Note	Mirrors	Securely installed both sides
	Ρ	F	N/A	Note		APBA Decal
	Р	F	N/A	Note	Slings	Good Condition, Certification tag or paperwork up to date
	Р	F	N/A	Note	Slings	Snap hooks or clevis attachment

Inspector:	APBA Number:	
Owner or Representative:	APBA Number:	